



CWST wraparound repair sleeve heat shrink kit, unpressurized, for 8 to 43 mm cable diameter, 500 mm long

- Excellent split resistance of the composite structure offers superior resistance to mechanical abuse during and after the installation
- Integrated moisture barrier completely reconstitutes the cable sheath construction

## Product Classification

<b>Regional Availability</b>	EMEA
<b>Product Type</b>	Heat shrink repair sleeve
<b>Product Series</b>	CWST

## General Specifications

<b>Color</b>	Black
<b>Sealant Type</b>	Hotmelt adhesive

## Dimensions

<b>Length</b>	500 mm   19.685 in
<b>Single Cable Diameter, maximum</b>	43 mm   1.693 in
<b>Single Cable Diameter, minimum</b>	8 mm   0.315 in
<b>Expanded Wall Thickness, minimum</b>	1.1 mm   0.043 in

## Material Specifications

<b>Material Type</b>	Fiber-reinforced multi-layer sealing sleeve
----------------------	---

## Environmental Specifications

<b>Environmental Space</b>	Aerial   Buried   Ducted
----------------------------	--------------------------

## Packaging and Weights

<b>Packaging quantity</b>	1
<b>Packaging Type</b>	Bag   Carton

## Regulatory Compliance/Certifications

**Agency**

CHINA-ROHS  
REACH-SVHC  
ROHS

**Classification**

Below maximum concentration value  
Compliant as per SVHC revision on [www.commscope.com/ProductCompliance](http://www.commscope.com/ProductCompliance)  
Compliant

