



ACBS

Air and water blocking system

ACBS is a unique Adhesive Cable Blocking system

- Air and water block
- No need to mix resin components
- Non-toxic components
- Fast, easy and clean installation
- Capability to block air-core cables up to 400 pairs
- Designed to be installed both vertically and horizontally
- No special tools required
- Installation quality indicator shows correct installation
- Tubular and wraparound versions, suitable for both, new constructions and maintenance
- Applicable for PE and PVC sheathed cables with both PE or PVC solid insulated conductors

Sizing/ordering information

Dimensions (in mm)

ACBS-T: selection chart for TUBULAR version

Description diameter*	Cable	
	maximum	minimum
ACBS-T-18/12	18	12
ACBS-T-24/18	24	18
ACBS-T-30/22	30	22
ACBS-T-40/30	40	30
ACBS-T-45/40	45	40

ACBS-W: selection chart for WRAPAROUND version

Description	Cable diameter*	
	maximum	minimum
ACBS-W -18/12	18	12
ACBS-W-24/18	24	18
ACBS-W-30/22	30	22
ACBS-W-40/30	40	30
ACBS-W-45/40	45	40

*Notes

For double jacketed cable, the cable dimensions refer to the inner jacket dimensions

For cables below 12mm diameter, please refer to the CBSM product line

Kit content ACBS-T



- Tubular sleeves (2 pieces)
- Blocking adhesive bags
- Tubular net
- Channelling pins
- Adhesive cable wraps
- Cleaning tissue
- Abrasive strip
- Installation instruction

Kit content ACBS-W



- Reinforced wraparound sleeves
- Channels (2 pieces)
- Blocking adhesive bags
- Wraparound net
- Channelling pins
- Aluminium cable protection foil
- Cleaning tissue
- Abrasive strip
- Installation instruction

Tyco Electronics and TE logo are trademarks.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, Tyco Electronics makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. Tyco Electronics' obligations shall only be as set forth in Tyco Electronics' Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of Tyco Electronics products should make their own evaluation to determine the suitability of each such product for the specific application.

Tyco Electronics Raychem bvba

Diestsesteenweg 692

3010 Kessel-Lo, Belgium

Tel 32-16 351 011 (USA)1-919-557-8900

Fax 32-16 351 697 (USA)1-919-557-8498

www.tycoelectronics.com

www.telecomosp.com

TC 317/DS/2 04/97

Tyco Electronics

Our commitment. Your advantage.