

F04656-000 | VCKT-90-3-INT



VCKT Vault Copper Closure, unpressurized, heat shrink, 510 mm joint length, 3 MDF cable outlets

- Vault closure system for the distribution of telecommunication cables in telephone exchanges
- Flexibility arises from selective use of break-out ports up to 3/9/12 or 24 MDF cables
- Vertical installation with re-entry option of the splice area for testing and measuring

Product Classification

Product Series	VCKT
Product Type	Unpressurized heat shrink closure
Regional Availability	EMEA

Body Features

Color	Black
Material	Fiber-reinforced multi-layer sealing sleeve
Sealant	Hotmelt adhesive

Configuration Features

Number of Cables, maximum	4
Splice Protection Type	Metal canister

Dimensions

Single Cable Diameter, minimum	12.00 mm		0.47 in
Length	800.00 mm		31.50 in
Sheath Opening, nominal	510.00 mm		20.08 in
Single Cable Diameter, maximum	36.00 mm		1.42 in
Splice Bundle Diameter, maximum	85.00 mm		3.35 in

Operation/Application

Environment	Aerial Central Office Direct burial
For Use With	Polyethylene and metal jacketed cables Standard splice connectors

Outline Drawing

Outline Drawing	Used as an image placeholder
-----------------	------------------------------

Packaging Features

Included	Abrasive strip Aluminum closing strip Aluminum tape Cleaning tissue Flexible stainless steel channels Heat-shrinkable sleeve Metal canister Shield continuity wire Underclips
Not included	Branch-off clip kit Crimp splice connectors
Packaging Method	Bag/Carton
Packaging Quantity	1



Your solution partner

VCKT VAULT
COPPER CLOSURE

F04656-000 | VCKT-90-3-INT

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant

*** Footnotes**

Number of Cables, maximum In/out branch cables at each end