

## 632764-000 | T2C-100-450-2/4-INT01



T2C Copper Closure, unpressurized, gel sealed, in-line, for up to 300 pair splices

- Watertight splice closure for aerial, underground and direct buried splices in the unpressurized copper telecommunication network
- Fast and easy installation and re-entry process with the gel-sealing system
- Robust and reliable under a wide variety of environmental conditions

### Product Classification

Product Series	T2C
Product Type	Gel sealed closure
Regional Availability	EMEA

### Body Features

Color	Black
Sealant	Gel filled

### Configuration Features

Number of Cables, maximum	4
Splicing Capacity	300 pair

### Dimensions

Height	165.60 mm		6.52 in
Length	695.00 mm		27.36 in
Sheath Opening, nominal	450.00 mm		17.72 in
Width	159.40 mm		6.28 in

### Operation/Application

Environment	Aerial   Direct burial
For Use With	Polyethylene cables

### Packaging Features

Included	Cleaning tissue   Closure   Gel sealing tape   Installation Instruction   Measuring tape   Mounting hardware   O-ring seal   Tie wraps
Packaging Method	Bag/Carton
Packaging Quantity	1

### Regulatory Compliance/Certifications

**Agency**  
RoHS 2011/65/EU

**Classification**  
Compliant

### \* Footnotes

Number of Cables, maximum In/out branch cables at each end