



FTUO Fiber Termination Unit Outdoor Wall Box with universal splice holder for 8 splices

- Typically used as a transition point where the OSP cable is spliced to an indoor cable
- Allows the installation of fibers with a minimum bend radius of 25 mm over a length of 2m
- In-line and single-ended enclosure configuration possible for main cable
- Cable inlet is provided at the bottom left side. Optionally the main cable can continue at the top left side
- Universal splice holder can hold SMOUV and ANT splice protector types

Product Classification

Regional Availability	EMEA
Product Type	Fiber wall box
Product Series	FTUO
Minimum Order Quantity	10

General Specifications

Functionality	Splicing
Access	Front
Application	For drop cables up to 5 mm diameter For main cables up to 12 mm diameter
Cable Entry Location	Back Bottom left Bottom right Top left Top right
Cable Ports, quantity	5
Enclosure Color	Gray
Lock Type	Locking screw
Mounting	Wall
Splicing Capacity, maximum	8

Dimensions

Height	168 mm 6.614 in
Width	132 mm 5.197 in
Depth	33 mm 1.299 in

Material Specifications

Enclosure Material Type	Polycarbonate + ASA
--------------------------------	---------------------

Environmental Specifications

Environmental Space	Outdoor
Flammability Rating	UL 94 V-0
Qualification Standards	IEC 60529, IP40 when cable enters from top IEC 60529, IP43 when cable enters from bottom
UV Resistance	UV stabilized

Packaging and Weights

Included	Hook and loop fastener Rubber seal Silicone tube Splice protector holder Tie wraps
Packaging quantity	1
Packaging Type	Box Carton

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant

