



SCIL-C Fiber splice closure, in-line, with 6 floating gel cable sealing kits, 1 pre-installed 48-splice tray and SMOUV protectors, no ground feedthrough Lug, no air valve

- Leverages proven FOSC™ fiber management system, with multiple splice tray options
- Removeable cover allows unrestricted access to cable termination and splice area for easier installation
- Cable termination and retention system fits any cable type from traditional loose tube buffered to small micro-sheath cables

Product Classification

Product Type	In-line, rectangular fiber closure
Regional Availability	Asia Australia/New Zealand EMEA Latin America North America
Product Series	SCIL-C
Product Brand	SCIL™

General Specifications

Splicing Type, Supported	Single fusion
Splicing Capacity, Single Fusion, maximum	288
Color	Black
Includes	SMOUV splice protectors (48)
Network Area Type	Drop
Package, quantity	1
Packaging Type	Box Carton
Splice Tray Included, quantity	1
Splice Tray Type Included	48-way, heat shrink
Splicing Capacity, Single Splice, 12 fibers, maximum	288

Dimensions

Main Cable Diameter, maximum	22.00 mm
Height	140.00 mm 5.51 in
Length	350.00 mm 13.78 in
Weight	1.00 kg 2.20 lb
Width	216.00 mm 8.50 in

Mechanical Specifications

Cable Sealing Type	Compressed gel
Cable Entry Drop Port Style	Round
Cable Entry Main Port Style	Round
Cable Ports, quantity	6

Closure Sealing Type	Side latch
Closure Style	In-line
Material Type	Rugged polymer
Mount Type	Pole Strand Wall

Environmental Specifications

Environmental Space	Above ground Below ground
Qualification Standard	IEC 60529, IP68 + 2 m waterhead

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

